




# Jäger Plus

HIGH PERFORMANCE  
MONOCRYSTALLINE PERC MODULE



## RSM144-6-395M-420M

**144 CELL**

Mono PERC Module

**395-420Wp**

Power Output Range

**1500VDC**

Maximum System Voltage

**20.9%**

Maximum Efficiency

### KEY SALIENT FEATURES



Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing



Industry leading lowest thermal co-efficient of power



Industry leading 12 years product warranty



Excellent low irradiance performance



Excellent PID resistance



Positive tight power tolerance



Dual stage 100% EL Inspection warranting defect-free product



Module Imp binning radically reduces string mismatch losses



Excellent wind load 2400Pa & snow load 5400Pa under certain installation method



Comprehensive product and system certification

- ♦ IEC61215:2016; IEC61730-1/-2:2016;
- ♦ ISO 9001:2015 Quality Management System
- ♦ ISO 14001:2015 Environmental Management System
- ♦ ISO 45001:2018 Occupational Health and Safety Management System



\* As there are different certification requirements in different markets, please contact your local Risen Energy sales representative for the specific certificates applicable to the products in the region in which the products are to be used.


### RISEN ENERGY CO., LTD.

Risen Energy is a leading, global tier 1 manufacturer of high-performance solar photovoltaic products and provider of total business solutions for residential, commercial and utility-scale power generation. The company, founded in 1986, and publicly listed in 2010, compels value generation for its chosen global customers. Techno-commercial innovation, underpinned by consummate quality and support, encircle Risen Energy's total Solar PV business solutions which are among the most powerful and cost-effective in the industry. With local market presence and strong financial bankability status, we are committed, and able, to building strategic, mutually beneficial collaborations with our partners, as together we capitalise on the rising value of green energy.

Tashan Industry Zone, Meilin, Ninghai 315609, Ningbo | PRC  
Tel: +86-574-59953239 Fax: +86-574-59953599  
E-mail: marketing@risenenergy.com Website: www.risenenergy.com

### LINEAR PERFORMANCE WARRANTY

12 year Product Warranty / 25 year Linear Power Warranty




\* Please check the valid version of Limited Product Warranty which is officially released by Risen Energy Co., Ltd



THE POWER OF RISING VALUE

## Dimensions of PV Module Unit: mm



## ELECTRICAL DATA (STC)

Model Number	RSM144-6-395M	RSM144-6-400M	RSM144-6-405M	RSM144-6-410M	RSM144-6-415M	RSM144-6-420M
Rated Power in Watts-Pmax(Wp)	395	400	405	410	415	420
Open Circuit Voltage-Voc(V)	48.45	48.60	48.75	48.90	49.00	49.10
Short Circuit Current-Isc(A)	10.40	10.50	10.60	10.70	10.80	10.90
Maximum Power Voltage-Vmpp(V)	40.35	40.45	40.55	40.65	40.70	40.80
Maximum Power Current-Imp(A)	9.80	9.90	10.00	10.10	10.20	10.30
Module Efficiency (%) *	19.7	19.9	20.2	20.4	20.7	20.9

STC: Irradiance 1000 W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

\* Module Efficiency (%): Round-off to the nearest number

## ELECTRICAL DATA (NMOT)

Model Number	RSM144-6-395M	RSM144-6-400M	RSM144-6-405M	RSM144-6-410M	RSM144-6-415M	RSM144-6-420M
Maximum Power-Pmax (Wp)	295.6	299.3	303.1	306.9	309.2	312.7
Open Circuit Voltage-Voc (V)	44.60	44.70	44.90	44.99	45.63	45.70
Short Circuit Current-Isc (A)	8.53	8.61	8.69	8.77	8.80	8.87
Maximum Power Voltage-Vmpp (V)	37.00	37.05	37.14	37.24	37.30	37.40
Maximum Power Current-Imp (A)	8.00	8.08	8.16	8.24	8.29	8.36

NMOT: Irradiance at 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1 m/s.

## MECHANICAL DATA

Solar cells	Monocrystalline
Cell configuration	144 cells (6×12+6×12)
Module dimensions	2015×996×40mm
Weight	23kg
Superstrate	High Transmission, Low Iron, Tempered ARC Glass
Substrate	White Back-sheet
Frame	Anodized Aluminium Alloy type 6063T5, Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm <sup>2</sup> (12AWG), Positive(+)350mm, Negative(-)350mm (Connector Included)
Connector	Risen Twinseal PV-SY02, IP68

## TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.29%/°C
Temperature Coefficient of Isc	0.05%/°C
Temperature Coefficient of Pmax	-0.37%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	20A
Limiting Reverse Current	20A



## PACKAGING CONFIGURATION

	40ft(HQ)	20ft
Number of modules per container	594	270
Number of modules per pallet	27	27
Number of pallets per container	22	10
Packaging box dimensions (LxWxH) in mm	2040×1130×1130	2040×1130×1130
Box gross weight[kg]	670	670

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

©2021 Risen Energy. All rights reserved. Contents included in this datasheet are subject to change without notice.

No special undertaking or warranty for the suitability of special purpose or being installed in extraordinary surroundings is granted unless as otherwise specifically committed by manufacturer in contract document.



Our Partners: